



Sensing Precision

Air Measurement Specialists

Product Datasheet

Wilson Flowgrid



Overview

Wilson Flowgrids are the most accurate flowgrid type within the product range. They are supplied to suit rectangular or round ducts. Wilson Flowgrids comprise of a number of tubes that span the whole duct area. Each tube has a number of flow sensing positions some of which face upstream and some downstream, hence the generation of the pressure differential. It is this vast array of sensing positions spanning the whole duct area that makes the Wilson Flowgrid the most accurate within the flowgrid range. By design all Wilson Flowgrids generate “enhanced” differential pressure signals.

Rectangular flowgrids are fabricated using two horizontal steel tubes and a number of vertical pressure sensing tubes which are bound together with Acetal plastic joints. The vertical tubes are positioned so that the pressure sensing ports in the tubes alternately face upstream and downstream. The two horizontal tubes then generate the averaged signal for both the upstream and downstream pressures, thus producing the differential pressure.

Radial flowgrids work in exactly the same way as rectangular flowgrids with the main difference between the two types being the method of fabrication. Unlike rectangular Wilson Flowgrids, radial Flowgrids are a fully welded stainless-steel construction. There are no plastic parts and so by default, are all high temperature graded, and compatible with some, but not all, chemical and harsh environments.

Applications

- In Duct Air Velocity Measurement
- In Duct Air Volume Flow Measurement
- BMS Primary Control Systems
- In process control for industries like pharmaceutical and food manufacturing

Specifications

Standards

Complies with relevant BS, ISO & EPA Sections

Variations

Standard, High Temperature & Containment suitable systems

Sizes

Rectangular

Up to 3m²

Circular

Up to 2.5m Ø

Uncertainty of Flow Measurement

±2% or better from onsite calibration

Temperature Range

Standard System

80°C Max

High Temp System

850°C Max

Materials

Standard System

Stainless Steel with Acetal Plastic Joints

High Temp System

Fully Stainless Steel

Special Systems

Polypropylene for harsh chemical environments.
Grids designed for high temperature applications.

Available Extras

Ducting, Flanges, Scaled Transmitter, Flow Straighteners

**We represent this supplier.
For more information contact
Observator Instruments:**

**T: +31 (0)180 463411
E: info@observator.com**

Rietdekkerstraat 6
2984 BM Ridderkerk
The Netherlands

Welcome to the world of Observator

Since 1924 Observator has evolved to be a trend-setting developer and supplier in a wide variety of industries. Originating from the Netherlands, Observator has grown into an internationally

oriented company with a worldwide distribution network and offices in Australia, Germany, the Netherlands, Singapore and the United Kingdom.

www.observator.com